

# Power Conditioner

120VAC 1Ph 480VA-2440VA



- Sizes Ranging from 480VA to 2440VA**  
 2 compact enclosure sizes span the entire product range.
- Transformer based design**  
 Standard with toroidal transformer to provide isolation within a small footprint.
- Complies with ANSI/IEEE C62.41**  
 Reduces normal mode noise to < 10V and common mode noise to < .5V.
- Surge Suppression**  
 Category A - 6000V @ 200A, 0.5 usec risetime, 100kHz  
 Category B - 6000V @ 500A, 0.5 usec risetime, 100kHz
- LED Indicator**  
 Bi-color LED signaling ground fault or loss of ground.



## Specifications:

MODEL	480 VA	720 VA	960 VA	1440 VA	1920 VA	2440 VA
Amperage Rating	4A	6A	8A	12A	16A	20A
Efficiency	> 90%					
Dimensions (LxWxH)	8.6"L x 7.0"W x 4.0"H			9.8"L x 8.2"W x 5.2"H		
Weight						
Input Voltage	120 VAC (Ph-N-G)					
Input Type	6ft 5-15R Cord / Hardwire			6ft 5-15R Cord / Hardwire		
Output Voltage	120 VAC (Ph-N-G)					
Output Type	(4) 5-15R Outlets / Hardwired			(6) 5-15R Outlets / Hardwired		
Compliance	UL 1012 / CSA-C22.2 No. 107.1 / ROHS					



Cord / Plug



Hardwired