

PLATINUM SERIES UPS

(1-3kVA)



True On-line Double Conversion Platinum Series UPS Series has been designed to support and protect various applications. Ideal backup system for VoIP, PBX systems, Telecom systems, small data centers and advanced control systems.

Engineered to support demanding applications

- **Available sizes**

1kVA, 1.5kVA, 2kVA and 3kVA units available

- 3kVA available in 208VAC

- **Variable Voltages (Input/Output)**

Available Voltages

(120VAC) input, (120VAC) output

3kVA (208VAC) input, (208VAC) output

- **Low Voltage and High Voltage Units**

The Platinum Series UPS systems will have low voltage units (1, 1.5/2/3kVA), and high voltage units (3kVA)

- **Tower or Rack Configurations**

These units are designed for 19" rack applications, and/or Tower (less footprint).

- **Conformal Coated Boards**

- Conformal coated boards allow for the Platinum Series to be used in "Light Industrial" applications. Boards that are conformal coated include the Main PCB, Comm., Charger and Control boards.

- **Input/Output Receptacles**

120VAC UPS

1kVA Input (NEMA 5-15P), (8) 5-15R receptacles

1.5kVA Input (NEMA 5-15P), (8) 5-15R receptacles

2kVA Input (NEMA 5-20P), (4) 5-15R's, (4) 5-20R's

3kVA Input (NEMA 5-30P), (4) 5-15R's, (4) 5-20R's

(1) L5-30R

208VAC UPS

L6-20P Detachable Input Power Cord, IEC C-20 inlet

(8) IEC C-13, (1) C-19 Receptacles

- **Internal Batteries**

All units include internal batteries. @ 3.5 minutes (at full load).

- **Extended Battery Cabinets**

All units are supported with additional battery backup by using the extended battery cabinets. Each battery cabinet includes power cord from battery cabinet to UPS.

- **2 Post Rail Kits**

UPS packaging includes feet for Tower set up. 2 Post Rail Kits are available as an option.

- **4 Post Rail Kits**

UPS packaging includes feet for Tower set up. 4 Post Rail Kits are available as an option.

- **Communication Cards**

Available Communication Cards include the following:

- Standard SNMP Protocol
- MODBUS Communication
- WiFi Communication
- Relay Card

- **Warranty**

Two (2) year warranty on the electronics and batteries. For additional warranty options please call factory.

- **Agency Standards**

All units are TUV Certified (tested to UL1778, 5th Edition, CSA22.2 No.107.3-14)

Specifications:

MODEL	1kVA(L)	1.5kVA(L)	2kVA(L)	2kVA(H)	3kVA (H)	
CAPACITY*	1kVA / 1kW	1.5kVA / 1.5kW	2kVA / 2kW	2kVA / 2kW	3kVA / 3kW	
INPUT						
Input Voltage Nominal Range	100-120VAC, 90-150VAC, (Low Voltage Units), 200-240VAC, 180-300VAC (High Voltage Units)					
Frequency Range	40/70 Hz +/-4%, (Auto sense on startup)					
Topology	True Online Double Conversion					
Input Current THD	<9.0%					
Power Factor	1/1.5/2/3kVA = 1:1 at 100% Load					
OUTPUT						
Phase	1 Phase					
Output Voltage / Low-High	(L) 100/110/115/120, (H) 200/208 /220 / 230 / 240, NOTE: (L) 120VAC Default, (H) 208V Default					
AC Voltage Regulation	± 1% (Normal)					
Frequency Range (Sync Range)	46Hz ~ 54 Hz @ 50Hz system, 57Hz ~ 63 Hz @ 60Hz system, (Batt Mode) +/- 0.1% Hz					
Overload	AC Mode/	100%~110%: 1 hour; 110%~130%: 1min; >130% : 1sec				
	Battery Mode	100%~110%: 30sec; 110%~130%: 10sec; >130% : 1sec				
Current Crest Ratio	3:1 max					
Voltage THD	≅ 2 % @ 100% Linear Load; ≅ 4 % @ 100% Non-linear Load (PF≥0.8)					
Step Load Response	+/- 4% 50% step load, +/-6% 100% step load, Return +/-3% of nominal (11 cycles)					
EFFICIENCY						
AC Mode	>89% @ fully charged batteries (1-1.5kVA)		>91% @ fully charged batteries (2-3kVA)			
BATTERY						
Voltage (VDC)	27.4VDC +/-1%,	41VDC +/-1%	54.7VDC +/-1%	82.1VDC +/-1%		
Battery Backup Time	@ 3.5 minutes at full load					
Charger Current	Default: 2A, Max: 8A adjustable					
Recharge Time	3 hours recovery to 95% capacity for internal battery @ 2A charging current					
PHYSICAL						
Standard Model	Dimension, W x D x H (In.)	17.3" x 16.2" x 3.4"	17.3" x 16.2" x 3.4"	17.3" x 24.8" x 3.4"	17.3" x 24.8" x 3.4"	17.3" x 24.8" x 3.4"
	Net Weight (lbs)	25.6 lbs	34.2 lbs	43 lbs	43 lbs	61.3 lbs
BYPASS						
Overload Conditions	Continuous below 130%, 1 minute at 130%, 1 cycle at 1000%					
ENVIRONMENT						
Operation Temperature	0 ~ 40°C					
Operation Humidity	<95 % and non-condensing					
Operation Altitude	2000 ft.					
Heat Dissipation (BTU/Hr)	520	877	1171	1000	1500	
Acoustic Noise Level (Front of Unit)	Less than 50dBA @ 1 Meter	Less than 50dBA @ 1 Meter	Less than 50dBA @ 1 Meter	Less than 50% dBA @ 1 Meter	Less than 50dBA @ 1 Meter	
MANAGEMENT						
Smart RS-232 or USB	Supports Windows® 2000/2003/XP/Vista/2008/7/8/10, Linux, Unix, and MAC					
Optional SNMP	Power management from SNMP manager and web browser					
MODBUS Card	Power Management with MODBUS communication					
AGENCIES						
RoHS	All units are RoHS compliant					
Safety Agencies	TUV Certified to comply to UL1778 5 th Edition, CSA22.2 No.107.3-14 UPS Safety Standards					
EMC	FCC Part 15J, Class A, IEC 61000-4-2, Electrostatic Discharge, IEC61000-4-3 Level 3 Radiated Electromagnetic Filed immunity. (Additional EMC Agencies listed in User's Manual).					